FIBRAINDATA STRUCTURED CABLING

SWD Wall mount two section cabinets

6U	SWD-06-500-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	500	330	19.5
9U	SWD-09-500-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	500	464	22.5
12U	SWD-12-500-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	500	600	26.3
15U	SWD-15-500-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	500	730	30.1
18U	SWD-18-500-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	500	865	33.9
21U	SWD-21-500-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	500	997	37.8



Cabinets

Features

- Standard RAL 9005 colour (black structure)
- \rightarrow
- Indoor use
- Wide range of additional accessories (pedestals, sockets, shelves, fan units, light units, light installing and placing the cables)
- 2x holes in the top part and the bottom to install ventilation panel
- Zinc sheet pair of vertical 19" mounting profiles, mounted on horizontal profile rails with 25 mm hole spacing
- Maximum spacing between mounting profiles:
 - → cabinet depth: 400 mm 335 mm,
 - → cabinet depth: 50 0mm 435 mm,
- Removable and lockable with single point lock side walls
- Front door with hardened glass (thickness: 3,15 mm) with single point lock, mounted on the hinges, opening angle 180° (optionally
- Left or right door opening options, \rightarrow
- 2x holes in the top part and bottom to insert
- Load capacity: 50 kg

Q Assembly set

- 1x brush strip
- 1x set of M6 rack bolts(16 pcs)
- \rightarrow 2x keys for side and back wall
- \rightarrow 2x keys for front door
- \rightarrow 4x set of M10 leveling feet
- 1.5 m of special edge sheath protecting cabling (after a breaking cable grommet)

Delivery

a secure portable carton on a wooden pallet

