SRS Floor Standing Cabinets

	SRS-22-6/6-S01-B						
22U	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	600	1095	53	300		
24U	SRS-24-6/6-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	600	1210	82	600		
24 U	SRS-24-6/8-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	800	1210	82	600		
27U	SRS-27-6/6-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	600	1315	60	600		
27U	SRS-27-6/8-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	800	1315	60	600		
32U	SRS-32-6/6-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	600	1535	73	600		
32U	SRS-32-6/8-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	800	1535	87	600		
32U	SRS-32-8/8-S01-B						
	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	800	800	1535	102	600		



	3K3 1L 0/ 0 30 L D						
42U	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	600	1980	88	600		
	SRS-42-6/8-S01-B						
42U	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	800	1980	105	600		
	SRS-42-6/9-S01-B						
42U	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	600	900	1980	110	600		
	SRS-42-8/8-S01-B						
42U	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	800	800	1980	121	600		
	SRS-45-8/8-S01-B						
45U	Width	Depth	Height	Weight [kg]	Load cap.[kg]		
	800	800	2120	130	600		

SRS-42-6/6-S01-B

Cabinets

+++ Features

- → Sheet steel housing, completely pre-assembled, self-ventilated, sheet steel/glass door,
- → Adjustable and removable side walls
- → Top and bottom part- perforation for fans
- → Standard RAL 9005 colour (black- structure)
- → IP20 protection
- → Sheet steel housing with welded frame
- → Housing has 4 entering points for cables (250x70m m) (1 x top part, 2x back part, 1x bottom part) with set of brushes
- → Front door: window made of safety glass with single point lock, mounted on the hinges, opening angle 180°
- → Left or right door opening options
- Zinc sheet pair of vertical mounting profiles 19", mounted on horizontal profile rails with 25 mm hole spacing, minimal distance from the front door 65 mm
- → Cords to ground front door (section: 6 mm, length: 300)
- → Can be arranged in sets with the use of ZLS
- → Wide range of additional accessories (pedestals, sockets, shelves, fan units, light units, light units, power distribution units, elements for installing and placing the cables)

Assembly set

- → 1x brush strip
- → 1x set of M6 rack bolts (16 pcs)
- → 2x keys for side and back wall
- → 2x keys for front door
- → 4x set of M10 leveling feet
- → 1,5 m of special edge sheath protecting cabling (after a breaking cable grommet)

Delivery

Cabinets are delivered as fully assembled items in

