FIBRAINDATA STRUCTURED CABLING

SWJ Wall mount single section cabinets

	SWJ-06-400-TOP-B			
6U	Width	Depth	Height	Weight [kg]
	600	400	330	19.1
90	SWJ-09-400-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	400	464	22.1
12U	SWJ-12-400-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	400	597	25.9
15U	SWJ-15-400-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	400	730	29.7
18U	SWJ-18-400-TOP			
	Width	Depth	Height	Weight [kg]
	600	400	860	33.5
21U	SWJ-21-400-TOP-B			
	Width	Depth	Height	Weight [kg]
	600	400	997	37.4





Cabinets

Features

- → Standard RAL 9005 colour (black structure)
- → IP20 protection
- → Indoor use
- → Wide range of additional accessories (pedestals, sockets, shelves, fan units, light units, light units, power distribution units, elements for installing and placing the cables)
- → 2x holes in the top part and the bottom to install ventilation panel
- → Zinc sheet pair of vertical 19" mounting profiles, mounted on horizontal profile rails with 25 mm hole spacing
- → Maximum spacing between mounting profiles:
 - → cabinet depth: 400 mm 335 mm,
 - → cabinet depth: 500 mm 435 mm
 - → cabinet depth: 600 mm 535 mm
- → Material: 1.25 mm thick steel sheet
- → Removable and lockable with single point lock side walls
- → Front door with hardened glass (thickness: 3.15 mm) with single point lock, mounted on the hinges, opening angle 180° (optionally steel door)
- → Left or right door opening options,
- → 2x holes in the top part and bottom to insert cables (250 x 70 mm)
- → Load capacity: 50 kg

Assembly set

- → 1x brush strip
- → 1x set of M6 rack bolts(16 pcs)
- → 2x keys for side and back wall
- → 2x keys for front door
- → 4x set of M10 leveling feet
- → 1.5 m of special edge sheath protecting cabling (after a breaking cable grommet)

Delivery

Cabinets are delivered as fully assembled items a secure portable carton on a wooden pallet

